

Technical Information Sheet



Nutshell Natural Paints Ltd.
Unit 3, Leigham Units
Silverton Road, Matford Park
Exeter, Devon, UK. EX2 8HY

Telephone: +44 (0) 1392 823 760

Fax: +44 (0) 1392 824 437

Email: enquiries@nutshellpaints.co.uk

NUTSHELL Aqua Undercoat

Revision: 1.5 2010-03-01

Product	NUTSHELL Aqua Undercoat is safe and easy to use, and provides a good ground to NUTSHELL Aqua Gloss and Satin paints. It can be used as a base coat for gloss paint for both interior and exterior wood and primed metal. It is formulated using natural plant oils which make the product much safer and more pleasant to use. NUTSHELL Aqua Undercoat has excellent coverage and flexibility which makes it easy to use. This product does not contain Volatile Organic Compounds (VOC).
Coverage	Coverage is approximately 8 - 10 sq. metres per litre. Coverage will vary considerably depending on method of application, surface roughness, weather conditions and complexity of structure.
Areas of use	Suitable for use on interior and exterior wood and primed metal.
Size	Available in 0.75 litre and 2.5 litre tins.
Preparation	Remove any loose or peeling paint. All bare wood should be primed with NUTSHELL Herb & Resin Oil, let to dry and lightly sanded before applying the undercoat. Any pre-painted surfaces should be lightly sanded before painting.
Application	Stir thoroughly before use. Apply one coat evenly. Allow this to dry and sand lightly. Apply a topcoat of NUTSHELL Aqua Gloss or Satin paint. NUTSHELL Aqua Undercoat can be applied using a brush, spray gun or roller.
Drying Time	Depending on the humidity and temperature the undercoat should be touch dry within approximately 2-4 hours. Allow 8 hours before applying your topcoat.
Thinning & Cleaning	Brushes and tools can be cleaned with soap and water.
Storage & Handling	Store in a cool, but definitely frost free place, in a well closed container. Always keep container closed and out of reach of children. Shelf Life: Approximately 6 months if opened otherwise about 2 years in unopened containers in a frost free store
Safety	<ul style="list-style-type: none">• As with all paints store well away from children and pets.• Avoid skin and eye contact. Wash eyes immediately with plenty of water if contact should occur.• Ensure good ventilation.• Close lid firmly after use.• Store and use away from heat and flame.• Do not eat in the vicinity of work.• Wash hands after use.



Nutshell Natural Paints Ltd.
Unit 3, Leigham Units
Silverton Road, Matford Park
Exeter, Devon, UK. EX2 8HY

Telephone: +44 (0) 1392 823 760

Fax: +44 (0) 1392 824 437

Email: enquiries@nutshellpaints.co.uk

NUTSHELL Aqua Undercoat

Revision: 1.5 2010-03-01

The information given in this Technical Information Sheet and any technical advice - whether verbal, in writing or by way of trials - is for guidance and is given in good faith but without warranty, since skill of application and site conditions are beyond our control. For further information please contact Nutshell Paints at the address shown above. We can accept no liability for the performance of the products arising out of such use, beyond the value of the goods delivered by us. This does not affect your statutory rights.