

Technical Information Sheet



Nutshell Natural Paints Ltd.
Unit 3, Leigham Units
Silverton Road, Matford Park
Exeter, Devon, UK. EX2 8HY

Telephone: +44 (0) 1392 823 760

Fax: +44 (0) 1392 824 437

Email: enquiries@nutshellpaints.co.uk

NUTSHELL Wallpaper Paste

Revision: 1.2 2010-01-25

Product	NUTSHELL Wallpaper paste is a cold water soluble glue for pasting wall papers, including the heavier types of paper, textile wall coverings etc on to absorbent surfaces.
Ingredients	The unmixed powder is 100% pure methyl cellulose fibres of different lengths.
Coverage	Priming: 100g added to 7 litres of water covers approximately 65 sq. metres. Normal papers: 100g added to 5 litres of water covers approximately 30 sq. metres. Heavy papers: 100g added to 4 litres of water covers approximately 15 sq. metres.
Areas of use	Most absorbent interior surfaces.
Mixing	Use the appropriate amount of cold water per 100 g powder. Sprinkle the powder into the cold water while stirring constantly and then keep beating until a lump free paste emerges. Leave the mixture to soak and expand for 30 minutes before mixing it again vigorously. The paste is now ready to use.
Size	Available in 100g and 500g packets.
Preparation	The surface to be decorated must be stable, absorbent, dry, clean and free of dust. Old wallpapers, wood chip papers, lime washes as well as loose oil and binder applications must be completely removed. Oil and binder applications which are still stable should be roughened with sand paper sufficiently to create an absorbent surface. Strongly absorbent surfaces should be prepared by applying a thin coat of paste and leaving it to dry, before hanging the paper with a further coat of paste.
Application	Apply paste to the wallpaper or other material by brush. Ensure that all edges of the paper are covered then stick the wallpaper to the wall. Smooth it out to expel any air bubbles, and then take special care to press the edges down well.
Drying Time	Depends on humidity, surface conditions and weight of paper.
Thinning & Cleaning	Clean tools with water immediately after use. Use water to further thin the paste if necessary.
Storage & Handling	Store dry unmixed powder in a closed container in a dry cool but frost-free place. Mixed paste can be stored in an airtight container indefinitely. Always keep container closed and out of reach of children.



Nutshell Natural Paints Ltd.
Unit 3, Leigham Units
Silverton Road, Matford Park
Exeter, Devon, UK. EX2 8HY

Telephone: +44 (0) 1392 823 760

Fax: +44 (0) 1392 824 437

Email: enquiries@nutshellpaints.co.uk

NUTSHELL Wallpaper Paste

Revision: 1.2 2010-01-25

Safety

- Store well away from children and pets.
- Avoid skin and eye contact. Wash eyes immediately with plenty of water if contact should occur.
- Ensure good ventilation.
- Close lid firmly after use.
- Store and use away from heat and flame.
- Do not eat in the vicinity of work.
- Wash hands after use.

The information given in this Technical Information Sheet and any technical advice - whether verbal, in writing or by way of trials - is for guidance and is given in good faith but without warranty, since skill of application and site conditions are beyond our control. For further information please contact Nutshell Paints at the address shown above. We can accept no liability for the performance of the products arising out of such use, beyond the value of the goods delivered by us. This does not affect your statutory rights.